

# **POWERING A WORLD** THAT'S ALWAYS ON 55

Our Integrated Solar Street Lights are included with Solar Panel, LED Lamp and the Li-Ion Battery into a single unit. It consumes lowenergy, runs longtime, very high luminance and maintenance free.

### **OPERATION**

Light will glow in full bright mode for first 4 hrs, after 4hrs light will dim to 33% power and motion sensor will activate to detection of motion. If any motion is detected in 12M area around the light, it will glow in full bright mode for 2 min, after that it will come to 33% power.

### **FEATURES**

Compact design with integrated Solar panel, LED light, motion sensor, Li-ion battery and Solar charge controller

Completely Off-Grid design with very easy installation

Microprocessor based design enables intelligent and efficient working

Lithium ion battery technology provides long and maintenance free product life

PIR Motion sensor adjusts brightness to extend light backup time

Automatic Dusk-to-Dawn operation and Solar panel dirty indication LED

# **INTEGRATED SOLAR** STREET LIGHT















### **Application**

- Airport Lighting
- Highway and roadway lighting
- Park and Playground lighting
- Industrial lighting and commercial lighting
- Outdoor security lighting

## **Technical Data**

MODEL		GKM-SIL15	GKM-SIL25	GKM-SIL45	GKM-SIL70	GKM-SIL100	GKM-SIL130		
LED PARAMETER	POWER	15W	25W	45W	70W	100W	130W		
	LED BRAND	OSRAM / SAMSUNG / LUMILEDS / EDISON / PHILIPS / CREE / SEOUL / NICHIA / EVERLIGHT							
	LUMINOUS	600 LM	900 LM	1800 LM	2400 LM	3000 LM	4000 LM		
	LIFE SPAN	50000 HOURS							
SOLAR PANEL PARAMETER	POWER	15-25 W	25-35 W	30-50 W	40-80 W	80-150 W	100-200 W		
	MATERIAL	HIGH EFFICIENCY MONO/ POLY CRYSTALLINE SILICON CELL							
	LIFE SPAN	25 YEARS							
BATTERY PARAMETER	CAPACITY	12.8V/10AH	12.8V/15AH	12.8V/20AH	12.8V/32AH	12.8V/40AH	12.8V/75AH		
	MATERIAL	PURE TERNARY, LOW INTERNAL RESISTANCE LITHIUM Po4 BATTERY WITH 5 YEAR WARRANTY							
	LIFE SPAN	5 YEARS							
OPERATION MODE	MODE	LIGHT DEPENDENT CONTROL	PR SENSOR & LIGHT DEPENDENT CONTROL  PR SENSOR & LIGHT DEPENDENT CONTROL  DELAYED INDUCTION & TIME CONTROL						
WORKING HOURS		2-3 DAYS							
SHELL MATERIAL		BAKING PAINT FOR IRON ALUMINIUM ALLOY FOR OXIDATION TREATMENT							
IP GRADE	CERTIFICATE	MNRE TESTED, CE, ISO 9000 & ISO 14000, BIS							
WARRANTY		2 YEARS / 5 YEARS							

# POWERING A WORLD THAT'S ALWAYS ON 33



Solar LED lights are a great option for lot lighting as they are off grid and require no trenching. MINDA SOLAR offers the most cost-effective, long-term solution to optimize the energy efficiency of your business or commercial property. Solar LED lights can help protect your business and pedestrians, better appealing to customers. Solar powered lights are the best solution of energy.



# SOLAR LED STREET LIGHT





### **Features**

- Dusk to down Operation.
- Deep discharge protection.
- Reverse Polarity protection
- Low Battery Indication.
- Battery Charging Indication.
- Reverse Polarity protection.
- Free of ultraviolet radiation.
- Dimmable Operation.









### **Application**

- Airport Lighting
- Highway and roadway lighting
- Park and Playground lighting
- Industrial lighting and commercial lighting
- Outdoor security lighting

# **Technical Data**

MODEL		GKM-SIL15	GKM-SIL25	GKM-SIL45	GKM-SIL70	GKM-SIL100	GKM-SIL130		
LED PARAMETER	POWER	15W	25W	45W	70W	100W	130W		
	LED BRAND	OSRAM / SAMSUNG / LUMILEDS / EDISON / PHILIPS / CREE / SEOUL / NICHIA / EVERLIGHT							
	LUMINOUS	600 LM	900 LM	1800 LM	2400 LM	3000 LM	4000 LM		
	LIFE SPAN	50000 HOURS							
SOLAR PANEL PARAMETER	POWER	15-25 W	25-35 W	30-50 W	40-80 W	80-150 W	100-200 W		
	MATERIAL	HIGH EFFICIENCY MONO/ POLY CRYSTALLINE SILICON CELL							
	LIFE SPAN	25 YEARS							
BATTERY PARAMETER	CAPACITY	12.8V/10AH	12.8V/15AH	12.8V/20AH	12.8V/32AH	12.8V/40AH	12.8V/75AH		
	MATERIAL	PURE TERNARY, LOW INTERNAL RESISTANCE LITHIUM Po4 BATTERY WITH 5 YEAR WARRANTY							
	LIFE SPAN	5 YEARS							
OPERATION MODE	MODE	LIGHT DEPENDENT CONTROL	PR SENSOR & LIGHT DEPENDENT CONTROL  PR SENSOR, LIGHT DEPENDENT CONTROL  DELAYED INDUCTION & TIME CONTROL						
WORKING HOURS		2-3 DAYS							
SHELL MATERIAL		BAKING PAINT FOR IRON ALUMINIUM ALLOY FOR OXIDATION TREATMENT							
IP GRADE	CERTIFICATE	MNRE TESTED, CE, ISO 9000 & ISO 14000, BIS							
WARRANTY		2 YEARS / 5 YEARS							

